



-Flexible souple HP DN3

Supple hose pipe HP, diameter 3 mm

-Ame PTFE - tresse inox , raccordements inox

-Ame PTFE - stainless steel packing and stainless steel connection

-Raccords: Double femelle Nato tournant, joint nylon dur

-Connection: two female turning Nato connection, with hard nylon joint

-Pression de service maxi: 300 bar (4350 psi)

-Maxi service pressure: 300 bar (4350 psi)

-Pression d'épreuve: 400 bar (5800 psi)

-Test pressure: 400 bar (5800 psi)

-Codification:

-Codification:

-LJNA 3027-XXXX

-LJNA 3027-XXXX

Où XXXX = longueur en mm

Or XXXX = length in mm

Exemple: LJNA 3027-2600 (L= 2600mm)

Exemple: LJNA 3027-2600 (L= 2600mm)

-Repère pour usage:

-Reference marks:

-GAINE DE COULEUR AUX EXTREMITES:

-Colour jackets at the ends:

-Azote = Noir

-Nitrogen = Black

-Air 3520 = Jaune

-Air 3520 = Yellow

-Skydrol = Magenta

-Skydrol = Magenta

-Oxygène = Blanc

-Oxygen = White

-Repère pour usage: Référence - longueur - fluide - numéro de série

-Used marks: Reference - length - fluid - serial number

Cable anti-fouet systématique pour longueur > 8000 mm

Anti - whip cable for length > 8000 mm hose pipe



LJP Industries
18, rue de la place
77410 CLAYE - SOUILLY CEDEX
Tel: 01.60.26.16.72
Contact: infos@ljpairo.com

FLEXIBLE HAUTE PRESSION
2x FEMELLE NATO TOURNANT
HIGH PRESSURE HOSE PIPE
2x FEMALE TURNING NATO

Creation Date:
2009/09/17

P/N: LJNA 3027

Sheet
1/1