



Raccord de liaison, HP, tournant, percuté, rallonge coudée

Connection joining HP turning, strike and rigid bent extension

Construction en acier inox

Built in stainless steel

Fluide standard: Azote

Standard fluid: Nitrogen

Raccordements:

Connections:

- Côté process: Femelle Nato tournant avec joint PTFE serrage à la clé

- Process side: Turning Nato female with PTFE sealing. To be tight with a spanner wrench

- Côté usage: Mâle Nato

- Used side: Nato male

Matière du joint d'étanchéité sur l'axe serrage: Viton

Viton ring for tight

Dimensions: voir figure

Dimensions: see above

Pression de service: 320 bar / 4800 psi

Operating pressure: 320 bar / 4800 psi

Pression de test: 400 bar / 5800 psi

Test pressure: 400 bar / 5800 psi

Option: Autres fluides sur demande

Option: Other fluid on request

Poids: 0,15 kg

Weight: 0,15 kg



LJP Industries
18, rue de la place
77410 CLAYE - SOUILLY CEDEX
Tel: 01.60.26.16.72
Contact: infos@ljpairo.com

**ROBINET PERCUTE 120°
NATO MALE / FEMELLE
120° LOCKING COUPLING
NATO MALE / FEMALE**

Photos et textes
non contractuels

Creation Date:
2009/09/10

P/N: LJNA 3029 PV HP

Sheet
1/1