



**-Flexible souple HP DN3**

**-Ame PTFE - tresse inox , raccords inox**

**-Raccords:**

**-Femelle Nato tournant, joint nylon dur**

**-Femelle M12x100 BNAE DN8**

**-Pression de service maxi: 300 bar (4350 psi)**

**-Pression d'épreuve: 400 bar (5800 psi)**

**-Codification:**

**-LJNA 3088-XXXX**

**Où XXXX = longueur en mm**

**Exemple: LJNA 3088-10000 (L= 10000mm)**

**-Repère pour usage:**

**-GAINE DE COULEUR AUX EXTREMITES:**

**-Azote = Noir**

**-Air 3520 = Jaune**

**-Skydrol = Magenta**

**-Oxygène = Blanc**

**-Repère pour usage: Référence - longueur - fluide - numéro de série**

**Cable anti-fouet systématique pour longueur > 8000 mm**

*Supple hose pipe HP, diameter 3 mm*

*-Ame PTFE - stainless steel packing and stainless steel connection*

*-Connection:*

*-Female turning Nato connection, with hard nylon joint*

*-Female M12x100 BNAE DN8*

*-Maxi service pressure: 300 bar (4350 psi)*

*-Test pressure: 400 bar (5800 psi)*

*-Codification:*

*-LJNA 3088-XXXX*

*Or XXXX = length in mm*

*Exemple: LJNA 3088-10000 (L= 10000mm)*

*-Reference marks:*

*-Colour jackets at the ends:*

*-Nitrogen = Black*

*-Air 3520 = Yellow*

*-Skydrol = Magenta*

*-Oxygen = White*

*-Used marks: Reference - length - fluid - serial number*

*Anti - whip cable for length > 8000 mm hose pipe*



**LJP Industries**  
18, rue de la place  
77410 CLAYE - SOUILLY CEDEX  
Tel: 01.60.26.16.72  
Contact: infos@ljpairo.com

**FLEXIBLE HAUTE PRESSION FEMELLE NATO  
TOURNANT / FEMELLE M12x100 BNAE DN8  
HIGH PRESSURE HOSE PIPE FEMALE TURNING  
NATO / FEMALE M12x100 BNAE DN8**

**Creation Date :**  
2010/02/22

**P/N : LJNA 3088**

**Sheet**  
1/1