



Raccord démontable pour maintenance.

Construction: Tout acier inox

Fluide standard: Azote

Raccordements:

-Côté flexible, mâle M12x100 BNAE DN8

-serrage six pans de 14.

-Côté process, femelle Nato tournant avec joint nylon dur

-serrage six pans de 12.

Pression maxi: 400 bar / 5800 psi

Dimensions:

-longueur hors tout: 38,1 mm

-Diamètre hors tout: 18 mm

Poids: 0,042 kg

Pièces détachées disponible

Dismantled connection for maintenace

Built in stainless steel

Standard fluid: Nitrogen

Connections:

-Fhose pipe connexion: M12x100 BNAE DN8 male

-14 mm six sided screwwing

-Process side female turning nato with hard nylon joint:

-12mm six sided screwing

Maxi pressure: 400 bar / 5800 psi

Dimensions:

-Maxi lenght: 38,1 mm

-Maxi diameter: 18 mm

Weight: 0,042 Kg

Spare parts on request



LJP Industries
18, rue de la place
77410 CLAYE - SOUILLY CEDEX
Tel: 01.60.26.16.72
Contact: infos@ljpairo.com

RACCORD
FEMELLE NATO TOURNANT / M12X100 MALE
ADAPTER
FEMALE NATO TURNING - MALE M12X100

Creation Date:
2009/09/09

P/N: LJNA 3013

Sheet
1/1